

7" COLOUR REAR VIEW CAMERA SYSTEM

CVWP-700 7" Colour Camera Kit (5.6" Monitor also available)



- 7 inch LCD TFT wide screen colour monitor.
- NTSC/PAL dual system monitor.
- Monitor has dual camera inputs.
- DC 12/24 Volt system.
- Quality high contrast image.
- Easy installation.



Monitor can be supplied with either 'fan foot' dash mount bracket, or 'stalk' style roof mount bracket.

SPECIFICATIONS

Colour Camera

- **Power Supply:** DC10V+/-0.5V
- **Power Consumption:** Max.2W
- **Image Pick-up Device:** 1/3" format CCD 250K pixels
- **Exposure:** Auto
- **White Balance:** Auto
- **Electronics Shutter:** 1/60s~1/100,000s
- **Video Output:** VBS 1Vp-p/75 Ohm
- **Audio:** Built in microphone
- **Operating Temperature:** -20~+50degC
- **Storage Temp:** -20~+70degC
- **Weatherproofing:** IP67 (body only)
- **Dimensions:** W82 x H49 x D56 mm
- **Weight:** 650g
- **Lens Furnished:** F=2.0 f=2.5mm
- **Field Angle:** Horizontal 115deg Vertical 84deg
- **Horizontal Resolution:** 380 TV lines or more (at image centre)
- **IR Luminary:** 5 pieces IR-LED 850mm
- **Min. Illuminate:** 0.3 Lux/F2.0

Colour Monitor

- **LCD Panel:** 7" TFT panel
- **Active Area:** 154.08 x 87.05
- **Display Format:** 480 x RGB x 234
- **DPI:** 0.107(H) x 0.372 (V)
- **Response time:** T on = 15ms (typ) T off 25ms (typ)
- **Brightness:** 350cd/m2(typ)
- **Contrast Ratio:** 350(min)
- **Viewing Angle:** B55deg (left & right) 15deg (top) 35deg (down)
- **LCD Panel Typ:** A-Si TFT Active Matrix
- **Operating Temp:** 0~+60degC
- **Storage Temp:** -20~+70degC
- **Dimensions:** W189 x H117 x D30.3 mm
- **Weight:** 500
- **Field Angle:** Horizontal 115deg Vertical 84deg
- **Power Supply:** DC12V/24V